

ACCESSORIES for HOISTS



[A]
Scaffold attachment for hoist
For better distribution of the stress on the scaffold caused by using the hoist. Equipped with plate for locking the work positioning lever.



[B]
Internal adjustable prop (2.45 m to 3.3 m)
For using the hoists indoors or where there are no external scaffolding structures; height adjustable from a min. of 2.45 m to a max. of 3.3 m.



[C]
Window prop
Useful at construction sites or for refurbishment jobs with little work space. Easy and quick installation without using assembly tools.



[D]
External prop
To install hoists outdoors without overhanging support points; consisting of an internal adjustable prop and conversion kit with ballast container.

| | | A | B | C | D |
|--|----|--------------|--------------|--------------|----------------|
| Max. capacity with extendible bracket hoist | kg | 200 | 200 | 200 | 200 |
| Max. capacity with fixed bracket hoist and swivelling extension | kg | 200 | 200 | - | 200 |
| Max. capacity with extendible bracket hoist and swivelling extension | kg | 150 | 150 | - | 150 |
| Weight | kg | 18 | 44 | 44 | 85 |
| W/l/h | mm | 210/180/1950 | 540/540/2630 | 640/340/1320 | 2505/1400/2630 |

ACCESSORIES for HOISTS

[E]

Gantries with capacity 300 kg (E1) and 500 kg (E2)

Suitable for all IMER hoists, except for RIO 100, Airone 200N and Airone 300N



[F]

Swivelling extensions:

- For prop clamp attachment with work positioning lever for Rio 100 (F1)
 - For prop hoist attachment with work positioning lever (F2)
- For lifting bulky material with fixed bracket hoists, allowing the loading distance to be increased 360 mm; for increasing the loading distance with extendible bracket hoists up to 1,480 mm, with carrying capacity reduced to 150 kg.



[F1]



[F2]

[G]

Hoist trolley



[H1]

Two-bucket carrier

[H2]

Four-bucket carrier



[I]

Three-way scaffold frame lifting hook



[L]

Wedge-shaped bucket 45/90/120 litres



[M]

Scaffold clamps



[N]

90-litre bucket with bottom discharge



| | | E1 | E2 | F1 | F2 | G | H1 | H2 | I | L | M | N |
|---------------|----|------|------|-----|-----|-----|-----|-----|----------|-------------|-----|-----|
| Max. capacity | kg | 300 | 500 | 100 | 200 | - | 70 | 150 | 60 | 150/200/300 | 200 | 200 |
| Weight | kg | - | - | 7 | 13 | 8 | 4/8 | 3 | 13/17/20 | 4.5 | 25 | |
| Width | mm | 2270 | 2280 | 120 | 90 | 450 | 340 | 820 | 65 | 400/420/450 | - | 660 |
| Length | mm | 3270 | 3270 | 700 | 680 | 875 | 810 | 820 | 360 | 460/615/720 | - | 660 |
| Height | mm | 2240 | 2280 | 445 | 275 | 430 | 450 | 450 | 410 | 310/370/430 | - | 720 |