

# BOOSTER 15

2-cylinder piston pump, hydraulic driven

## APPLICATIONS

For pumping concrete and self levelling floor screeds and for shotcreting.



**Booster 15**  
Cod. 1106120



**Booster 15 R**  
(towable version)  
Cod. 1106121



**Compact dimensions,**  
easy on-site transport  
and better handling



Well-soundproofed  
engine compartment



Pump with exclusive SOFT  
SPRITZ system to ensure  
high pumping performance  
also at low flow rates



## CONTROL PANEL



ANTISHOCK control panel with  
electromechanical controls

## Standard Equipment

- ✓ Liquid cooled Diesel engine - 21.2 kW
- ✓ Concrete hopper with agitator
- ✓ Grid with 12V vibrator
- ✓ Hydraulic system with reversing
- ✓ Pumping unit with S-tilting valve for automatic compensation of clearance and wear
- ✓ 4" Victaulic delivery manifold (Ø 100 mm)
- ✓ Control panel with electromechanical controls
- ✓ Four-function remote control via cable
- ✓ Pumping piston replacement kit
- ✓ Drawbar for non-towable version
- ✓ Road-towable drawbar, parking brake and light units (road-towable version)
- ✓ Accessory box
- ✓ Grease pump



✓ Openable and tiltable taper hopper for simplified cleaning operations and easy maintenance

✓ 2-cylinder piston pump, hydraulic driven



Supply	-	Diesel engine
Installed power rate	kW	21,2
Pumping system	-	Two-cylinder with hydraulic control
Max grain size	mm	25
Flow rate (*)	m <sup>3</sup> /h	2-15
Pumping pressure (*)	bar	70
Pipe outlet	-	Victaulic 4"
Hopper capacity	l	240
Loading height	mm	1080
Dimensions width/length/h (towable version)	mm	1495/4100/1540
Weight	kg	1550

\*NOTE The max flow rate and the max pumping pressure cannot be performed at the same time.