

ET 500 N ET 500 TF ET 1000

Stand hoists – capacity 500 and 1000 kg

ET 500 N Standard Equipment

- ✓ Single-phase 230V/50Hz electric motor
- ✓ Swivel hook with leading block with cast iron pulley
- ✓ Double pull rope
- ✓ IP67 plug
- ✓ Frame with 4 aluminium wheels
- ✓ Upper limit safety device
- ✓ Direct control with 3-pushbutton 1.5-m pendant control
- ✓ Positioning brake
- ✓ Self-braking motor with magnetic device

Applications

Double pull hoist with transverse drum. High capacity and extremely versatile. The gearmotor is built with helical-toothed steel gears in oil bath.

ET 500 TF/ET 1000 Standard Equipment

- ✓ Three-phase 400V/50-60Hz electric motor
- ✓ IP67 plug
- ✓ Frame with 4 steel wheels
- ✓ Upper limit safety device
- ✓ Direct control with 3-pushbutton IP65 1.5-m pendant control
- ✓ Positioning brake
- ✓ Self-braking motor with magnetic device

NEW

Applications

Thanks to its sturdy structure and powerful motor, ET 1000 is particularly suitable for heavy duty use on site.



ET 500 N

Double pull rope
with cast iron pulley



ET 500 TF



ET 1000

		SINGLE-PHASE	THREE-PHASE	THREE-PHASE
		ET 500 N*	ET 500 TF*	ET 1000*
Maximum capacity	kg	500	500	1000
Av. full load lifting speed	m/min	10	20	10
Max. working height	m	21	42	21
Ø wire rope	mm	5	5	6
Rope length	m	43	43	43
Motor power rate	kW	1.1 (230V/50Hz)	2.2 (400V/50-60Hz)	2.2 (400V/50-60Hz)
Motor speed	rpm	1320	1320	1320
Motor running current	A	10	7	7
Machine weight	kg	50	71	75
SPL in operator's position	dB(A)	<74 (1.5 m)	<72 (1.5 m)	<72
Dimensions w/l/h	mm	340/800/390	380/800/410	382/800/410
Packing dimensions w/l/h	mm	380/810/420	380/810/420	400/820/440

* AVAILABLE ONLY FOR NON-EU COUNTRIES



ET 500 N on a gantry