MIX 120 plus

Compact mixer with planetary mixing system



Advantages

- Maximum safety for the operator: an electric device stops paddle rotation when the grid rises
- √ Ease in discharge operations and moving material thanks to the upper wheels and the extendable handles
- Homogeneous mix in short time using the forcedduty planetary mixing system with optimized profile paddles. No air is mixed with product
- High power, improved speed and reversible paddle rotation at any time ensure optimized mix also with difficult products to batch (semi-dry mixtures and tixotropic products)
- √ Adjustable discharge height, thanks to the extendible legs (max./min. 677/612 mm)

Standard equipment

- Single-phase motor 230V/50Hz -Gearbox in oil bath and high performance Poly-V transmission belt
- Electric safety limit switch
- Switch with overheat safety system, insulation class IP 55, no-volt coil and IP67 plug
- Paddle rotation reversing gear
- Grid with bag-splitting blades
- extendable handles
- Lifting hooks
- Additional wheels



Forced-duty planetary system for a remarkable batch time reduction

Powerful and versatile, Mix 120 plus batches the most difficult products, both traditional and pre-mixed materials





Discharge opening (view from below)

| Technical specifications | | |
|---------------------------|-------|-------------------------------|
| Drum capacity | litre | 120 |
| Actual yield | litre | 90 |
| Drum diameter | mm | 745 |
| Max grain size | mm | 8 |
| Paddle speed | rpm | 38 |
| Motor power rate | kW | 1,4 kW |
| Running current | Α | 9 |
| Lp in operator's position | dB(A) | 70 |
| Machine weight (boxed) | kg | 130 (139) |
| Dimensions w/l/h (box) | mm | 745/842/1277 (770/880/955) |