



GV-3000

GV-7000S

DURABLE AND HIGH PERFORMANCE




- **High Fuel Efficiency**
Powered by K210 & K420
- **100% Copper Wire for Alternator**



Copper Wire

- **Minimize Temperature**
- **Anti-Rusty Fuel Tank**


Specification

Model		GV-3000	GV-3200	GV-7000S	GV-7600S	
Model		KOSHIN K210		KOSHIN K420		
Type		Air-cooled, 4-Stroke, OHV, single cylinder				
Displacement(CC)		212 cc		420 cc		
Engine oil volume(L)		0.6 L		1.1 L		
ENGINE	Rated power	3.4 kW / 3000 rpm 3.7 kW / 3600 rpm		6.85 kW / 3000 rpm 7.6 kW / 3600 rpm		
	Maximum power	4.2 kW / 3600 rpm		8.5 kW / 3600 rpm		
	Max.torque	12 Nm / 2500 rpm		25 Nm / 2500 rpm		
	Fuel consumption(cc/h)	337 (g/kw/h)		370 (g/kw/h)		
	Starting System		Recoil		Recoil+Electric Starter	
	CONTROL PANEL	Receptacle	50Hz	 CEE 7/4 X 2		 CEE 7/4 NEMA L6-30
220V				60Hz	 BS1363 X 2	
		Phase			Single	
DC output(V-A)		12 V 8.3 A				
Rated Voltage(V)		220				
GENERATOR	AC output(kVA)					
	Rated	2	2.3	5	5.5	
	Maximum	2.2	2.5	5.5	6	
	Rated Frequency	50 Hz	60 Hz	50 Hz	60 Hz	
	AMPS	9.1 A	10.5 A	22.7 A	25 A	
Battery		-		Maintenance-free type		
Package Size(W*D*H)		640 X 475 X 485 (mm)		720 X 550 X 560 (mm)		